

REMOTE SENSING AS A TOOL FOR SUPPORTING LANDSLIDE RISK ANALYSIS

D. Colombo (1), P. Farina (2), A. Fumagalli (1), E. Gontier (3), P. Manunta (4), S. Moretti (2)

(1) Tele-Rilevamento Europa, TRE s.r.l., a POLIMI spin-off company, Milano, (2) Earth Sciences Dept., University of Firenze, (3) Spacebel, Angleur (Liège), (4) Planetek Italia s.r.l., Bari
paolo.farina@geo.unifi.it/Fax: +39-055-2756296

Keywords: Landslide risk , remote sensing, SAR interferometry

Within the framework of the SLAM project, funded by the European Space Agency (ESA), and aimed to the definition of a service based on the integration of EO-data within the current practices of landslide mapping and monitoring both optical and radar images have been analyzed in order to extract information to be integrated with traditional methods. In particular, the Permanent Scatterers processing and the analysis of high resolution images (e.g. SPOT5 and aerial-photos) have been performed at a basin scale, on the whole territory of the Arno River basin (Central Italy). The drainage basin of the Arno River is almost entirely situated within Tuscany. The river is 241 km long, while the catchment has an area of about 8830 km² and a mean elevation of 353 m a.s.l. The test basin, chosen for the presence of a high number of mass movements (up today about 300 areas at high landslide risk and more than 20,000 individual landslides mapped from the institutional authorities), are representative of the Italian Apennine territory, in terms of landslide type and environmental conditions. By considering the technical requirements imposed by the Italian legislation for the documents related to landslide risk management, three products based on EO-data have been defined related to landslide inventory mapping, landslide hazard mapping and landslide monitoring. To this aim, about 350 SAR images have been interferometrically processed by means of the PS technique, detecting about 600,000 PS. The processing of SPOT5 images and aerial-photos, still in progress, have been performed for the extraction of features related to the landslide presence, useful for the geomorphological analysis, in order to give a spatial meaning to the punctual information provided by the PS. This procedure has been coupled with a intense geological interpretation phase characterized by the analysis of traditional in situ monitoring data, ancillary data and the performing of field surveys. The results obtained up today have been intensely validated in collaboration with the local users and the comparison with traditional geotechnical data and the observations coming from field checks have confirmed the effectiveness of the methodologies. Such results have obtained a very high qualification ranking also from the users. The final results will impact on the current instruments used by the Arno Basin Authority for the landslide risk management (e.g. Hydrogeological Structure Plan - Piano per l'Assetto Idrogeologico – PAI) representing one of the first examples in Europe of full integration of remote sensing data into land regulations concerning landslide hazard.